

m9400 Media Player

Single 4K UHD AV (HDMI) out



The m9400 Media Player delivers interactive user portals and advanced network video decoding. Its fanless design, PoE functionality and low power consumption make it an economical choice for environments where premium video quality is important.

Video Output

- HDMI v2.0 (with HDCP 1.4 & 2.2):
 - 2160p (24Hz/50Hz/60Hz)
 - 1080p, 1080i, 720p (50Hz/59.94Hz/60Hz)
 - 576p, 576i (50Hz)
 - 480p, 480i (59.94Hz/60Hz)
- HDR Support:
 - HDR10
 - HLG

Audio Output

- HDMI: 2 or 8 channel PCM or Bitstream

Video Decoding

- H.265 HEVC main and main 10 profiles (ISO/IEC 23008-2). Resolutions up to UHD 2160p60
- MPEG-4 part 10 H.264 (ISO/IEC 14496-10). Resolutions up to Full HD 1080p60
- MPEG-2 (ISO/IEC 13818-2). Resolutions up to Full HD 1080p60

Audio Decoding

- MPEG-1 Layer II (ISO/IEC 11172-3)
- AC3/EAC3
- AAC-LC/HE-AAC
- Downmixes multi-channel audio to stereo
- Dolby Digital and Dolby Digital Plus pass through

Streaming

- MPEG 2 Transport Stream (ISO/IEC 13818-1)
- UDP / RTP
- HLS Live and VoD
- SRT
- IP multicast, IP unicast

Infra-red/Control Options

- Built-in IR receiver
- 3.5mm jack for IR extender
- TV on/off control using HDMI CEC

Features & Benefits

- Support IPTV streams up to 4K for excellent image quality
- Enable viewers to enjoy live and recorded TV, movies, information and more, all accessed via user interfaces created with ArtioView, our interactive IPTV technology solution
- Quiet, fanless design
- Plug-and-play connectivity with Power over Ethernet (PoE)
- Stream playback synchronised across multiple media players
- Built-in AV mode finds and displays TV and radio channels within a minute of initial startup

Integrated Web Browser

- Ekioh TV Browser for digital signage and integration with third-party middleware
 - HTML 5
 - CSS 3 & DOM 3
 - Image formats: PNG, JPEG

Content Protection

- Decryption of HDCPv2.2 protected content

Channel Management

- Channel selection and volume/mute control through either:
 - Avedia Server Smart Control application (ArtioView portals)
 - AV mode middleware (TV and radio channels)
- SAP/SDP announcements
- Optional channel import (static channels) in AV mode

Plug and Play

- Built-in AV mode middleware finds and displays TV and radio channels within a minute of initial startup

Accessibility

- DVB subtitles (ETSI EN 300 743)
- Teletext subtitles (ETSI EN 300 706)
- Closed captions (CEA-608 captions embedded in CEA-708 data)

Security

- Management using HTTPS connection
- Firmware upgrade using VITEC-signed upgrades only
- Secure hardware platform

Management

- HTTP/HTTPS device web interface; recommended browser: Chrome®
- Console access via SSH and Serial RS232 Admin Port
- Event logging via Syslog (local and remote)
- Day-to-day management using Avedia Server Smart Control:
 - Reboot
 - Publish signage
 - Set channel
 - Set volume
 - Turn on/off
- Administration using Avedia Server Site Manager:
 - Upgrade
 - Set name and location
 - Configuration import/export
 - Advanced RESTful configuration through the Site Manager Command Sender

Network

- Linux IPv4 stack
- DHCP IP addressing
- IEEE 802.3u 10/100Mbps MDIX Ethernet
- IEEE 802.3af PD

System

- Linux-based

Options

- TV and wall mounting brackets
- External AC-DC Power supply for non-POE environments
- IR remote controls and extenders

Additional Features

- Accelerated channel change mode (sub 500ms (transcoder required))
- Unit-to-unit sync capability

Protocols

IP (RFC791), UDP (RFC768), TCP (RFC793), ARP (RFC826), DNS (RFC1035), DHCP (RFC2131), ICMP (RFC0792), IGMP v3 (RFC 3376), HTTP (RFC2616), Syslog (RFC3164), NTP (RFC1305), HLS, SSDP, SRT

Environment

- Operating temperature: 0 ...+40°C / +32 ... +122°F
- Storage temperature: -20 ...+70°C / -4 ... +158°F
- Operating Relative Humidity: 5 – 95% (non-condensing)

Dimensions

- 45mm (H) x 200mm (L) x 140mm (D)

Weight

- 0.8 kg

Power

- DC Jack (24V): 10W typical, 12W maximum
- POE IEEE 802.3af PD (48V): 10W typical, 12W max

Regulatory

- CE:
 - IEC 62368-1: 2014
 - EN 62368-1:2014+A11:2017
 - EN55032:2012 + corrigenda Aug 2012 & Dec 2012
 - EN55024:2010 + A1:2015
 - EN 61000-3-2:2014
 - EN 61000-3-3:2013
- UL/CSA:
 - UL62368-1:2014
 - CSA C22.2 No. 62368-1, Rev. December 01, 2014
- FCC:
 - 47CFR:2011 Part 15, Sub Part B
 - ANSI C63-4:2014
- ACMA:
 - AS/NZS 62368.1.2014 (ed.2)

MTBF

- Calculated to MIL-HDBK-217F, notice 2: 101276 hours (11.6 years)

ArtioView

The m9400 Media Player has been designed specifically for use with ArtioView. It enables organisations to deliver a captivating video experience through advanced network video decoding and 4K video capability. It offers the following:

- Live TV channels
- Programme Guide
- Video on Demand
- Channel recording
- Video sharing
- Video on page
- Information pages
- View (create layers)
- Room service
- Hotel services
- RSS feeds
- TV apps
- Guest (PMS required)
- Language selection
- Welcome message
- Date/Time
- Excursions (PMS required)
- Mailbox
- Weather

In the Box

- m9400 Media Player, single 4K UHD AV (HDMI) out, PoE (802.3af); includes ArtioView client licence
- Product Safety Brochure (hard copy)

Ordering Information (P/N)

- 06062 (avply-9400) - Single 4K UHD AV (HDMI) out